

RRC-PS100

供电电源AC/DC

P/N: 212532



特点

- 100.00瓦标准电源供全球使用
- 操作简单
- 可提供国家专用的交流输入电缆

应用

适合与笔记本电脑，手持数据采集POS，测试和测量和其他工业应用。

技术参数

输入		
电压范围	100.00 – 240.00VAC ± 10%, 50-60HZ	
输入电流	最大 1.90A	
待机功率	无载 < 0.15W	
输出		
电压	20.00VDC ± 5%	
功率	最大 100.00W	
电流	最大 5.0A	
保护	短路, 过流, 过压保护, 过温	
环境参数		
环境温度	工作状态: 0°C 到 40°C	非工作状态: -30°C 到 80°C
压力和高度	1060hPa 到 533hPa -382m 到 5000m	1060hPa 到 533hPa -382m 到 5000m
湿度 (无凝结)	5% 到 90% r.H.	5% 到 90% r.H.
机械细节		
外壳尺寸 (长x宽x高)	127 x 51 x 30mm	
输出电缆长度	1600mm ±50mm	
重量	325g ± 5%	
交流输入接口	IEC 320 C6 Type	
输出连接器	DC圆头插口, 5.5 x 2.5 x 10mm	
总体参数		
能效	加州能源效率VI级	
冷却	对流冷却	
环保采购	RoHS 2011/65/EU + 2015/863/EU REACH 1907/2006 WEEE 2012/19/EU Chinese RoHS	
平均故障时间	100,000h, 环境温度25°C	
涟漪 & 噪音	380mV (p-p)	
安全与电磁兼容性		
监管机构批准	欧洲 国际 美国 & 加拿大 澳大利亚& 噶嘻蓝 俄罗斯 &欧亚关税同盟 韩国 中国 日本 印度 台湾 墨西哥 新加坡 阿根廷 南非 摩洛哥 以色列 泰國	EN62368-1 (CE) IEC62368-1 (CB) FCC, cULus RCM EAC KC CCC PSE BIS BSMI NOM Safety Mark IRAM SABS CMIM SII TISI
电磁辐射	欧洲 美国 加拿大 韩国	EN55032, EN55024 FCC15 class B ICES-003 KCC
电磁抗扰度	防静电 电磁抗扰度 EFT / 爆破 浪涌 传导免疫 磁场 电压骤降	EN/IEC61000-4-2 EN/IEC61000-4-3 EN/IEC61000-4-4 EN/IEC61000-4-5 EN/IEC61000-4-6 EN/IEC61000-4-8 EN/IEC61000-4-11
能效	DOE	

推荐附件

种类	产品	P/N	应用
三孔AC-电缆	美版	210950	国家专用电力电缆
	欧版	210951	
	英版	211133	
	澳版	211134	
	中国	211959	



德国/总部

RRC power solutions GmbH

Technologiepark 1
66424 Homburg / Saar

+49 6841 98090
sales@rrc-ps.com

美国

RRC power solutions Inc.

18340 Yorba Linda Blvd.,
107-437
Yorba Linda, CA 92886

+1 714 777 3604
usa@rrc-ps.com

香港

RRC power solutions Ltd.

S-V,6/F, Valiant Industrial
Centre 2-12
Au Pui Wan Street
Fo Tan, N.T., Hong Kong

+852 2376 0106
hkrrc@rrc-ps.cn

中国

RRC power solutions Ltd.

Room 1306, C Building,
Tianan International
Building, Renmin South
Road, Luohu District,
Shenzhen 518021

+86 755 8374 1908
hkrrc@rrc-ps.cn

越南

RRC Power Solutions
Company Ltd.

Block C, Lot CN4
Dinh Vu – Cat Hai
Economic Zone,
Dong Hai 2 Ward
Hai An District 180000
Hai Phong City

vietnam@rrc-ps.com